

# TBCC Discipline Overview

The “National Aeronautics Research and Development Policy”<sup>1</sup> document, issued by the National Science and Technology Council in December 2006, stated that one (among several) of the guiding objectives of the federal aeronautics research and development endeavors shall be stable and long-term foundational research efforts. Nearly concurrently, the National Academies issued a more technically focused aeronautics blueprint, entitled: the “Decadal Survey of Civil Aeronautics - Foundations for the Future.”<sup>2</sup> Taken together these documents outline the principles of an aeronautics maturation plan. Thus, in response to these overarching inputs (and others), the National Aeronautics and Space Administration (NASA) organized the Fundamental Aeronautics Program (FAP), a program within the NASA Aeronautics Research Mission Directorate (ARMD). The FAP initiated foundational research and technology development tasks to enable the capability of future vehicles that operate across a broad range of Mach numbers, inclusive of the subsonic, supersonic, and hypersonic flight regimes.

The FAP Hypersonics Project concentrates on two hypersonic missions: (1) Air-breathing Access to Space (AAS) and (2) the (Planetary Atmospheric) Entry, Decent, and Landing (EDL). The AAS mission focuses on Two-Stage-To-Orbit (TSTO) systems using “air-breathing” combined-cycle-engine propulsion; whereas, the EDL mission focuses on the challenges associated with delivering large payloads to (and from) Mars. So, the FAP Hypersonic Project investments are aligned to achieve mastery and intellectual stewardship of the core competencies in the hypersonic-flight regime, which ultimately will be required for practical systems with highly integrated aerodynamic / vehicle and propulsion / engine technologies. Within the FAP Hypersonics, the technology management is further divided into disciplines including one targeting Turbine-Based Combine-Cycle (TBCC) propulsion. Additionally, to obtain expertise and support from outside (including industry and academia) the hypersonic uses both NASA Research Announcements (NRA’s) and a jointly sponsored, Air Force Office of Scientific Research and NASA, National Hypersonic Science Center that are focused on propulsion research. Finally, these two disciplines use selected external partnership agreements with both governmental agencies and industrial entities.

The TBCC discipline is comprised of analytic and experimental tasks, and is structured into the following two research topic areas: (1) TBCC Integrated Flowpath Technologies, and (2) TBCC Component Technologies. These tasks will provide experimental data to support design and analysis tool development and validation that will enable advances in TBCC technology



# TBCC Discipline Overview

## *Hypersonics Project*

---

Scott R. Thomas  
Technical Lead, TBCC Discipline  
NASA Glenn Research Center, Cleveland, Ohio

2011 Technical Conference  
March 15-17, 2011  
Cleveland, OH



# OUTLINE

---



- Benefits of TBCC Propulsion
- Technical Challenge
- TBCC Discipline Roadmap
- Technology Approach
- Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX) in NASA GRC 10X10 SWT
- Integrated Flowpath Computational Efforts
- High Mach Fan Rig Testing in NASA GRC W8 Compressor Facility
- Component Technology Computational Efforts
- High Mach Turbine Engine Development
- Summary and Concluding Remarks

# TBCC Propulsion Benefits : Efficiency, Safety, Reliability



## ➤ High structural mass fraction providing large margins



- ✓ Design for life – Low Maintenance & High Durability
- ✓ Design for safety
- ✓ Re-usable > 1000 missions

## ➤ Horizontal takeoff and landing enhances launch, flight and ground operability

- ✓ Benign ascent abort/engine out
- ✓ Launch Pad not needed
- ✓ Flexible Operations & Quick Turn Around Time (Aircraft Like Operations)

$$I_{SP} = \text{Thrust/Pound per second of propellant (fuel) flow rate}$$


## Airbreathing Propulsion Significantly Increases Propulsion Efficiency



# Technical Challenge: Develop Airbreathing Turbine Based Combined Cycle Propulsion for TSTO Vehicles



Fully Integrated Inlet / Engine / Vehicle



- Develop Integrated TBCC Propulsion Technology – Inlet, High Mach Turbine Engine, Dual Mode Scramjet , Nozzle
- Establish a stable mode transition process while maintaining Propulsion System performance & operability
- Perform a stable controlled mode transition
- Avoid inlet and/or engine unstart
- Mitigate low/high speed inlet/engine interactions.
- Account for backpressure and cowl positioning effects.
- Develop, Validate, & Utilize design tools to optimize the configuration

# TBCC Discipline Roadmap



FY09	FY10	FY11	FY12	FY13	FY14	FY15
<b>TBCC Integrated Flowpath</b>		Inlet Performance	Data to GNC	Mode Transition w/ control	Inlet & Engine Mode Transition w/ control	2 <sup>nd</sup> Generation LIMX
<b>CCE Mode Transition Testing</b>		◆ ◆	◆	◆		◆
		Inlet Dynamics	Controller Delivered	Controller Delivered		PARTNERSHIPS REQUIRED
<b>Design, Analysis &amp; Dynamic models</b>		◆	◆		◆	
		Rapid Flowpath Design Tools	System Dynamics Models		Design Tools Validated	
<b>TBCC Component Technology</b>		Mach 3 Turbine Engine Delivered		Fan Validation Complete		
<b>Fan Operability &amp; Inlet Distortion</b>		◆ ◆	◆			
Uniform Flow		Distorted Flow			2 <sup>nd</sup> Generation Small Scale IMX	
<b>Bleed modeling</b>			◆	◆	◆	◆
			Parametric Experiments	Bleed Model Updated		

# TBCC Technology Approach



Propulsion

M & S

GNC

**Supporting  
Disciplines**

***Integrated  
Propulsion  
System  
Design &  
Analysis  
Tools***

**Validated  
Tools**

MDAO

## ***Partnerships & Collaboration***

- AFRL/Aerojet TBCC inlet tests
- DARPA/AFRL Facet / MoTr, et al
- RATTLS - inlet /controls
- AFRL/ WI High Mach Turbine

## ***Ground Experiments***

CCE LIMX Testing in the GRC  
10x10 SWT (4 phases)

High Mach Fan Rig testing in  
GRC W8 Compressor Facility

Inlet Bleed Studies in GRC  
15X15 cm & 1X1 ft SWT facility

## ***Integrated Flowpath: Computational Efforts***

CCE Low Speed Flowpath

CCE High Speed Flowpath &  
Isolator

## ***Component Technologies: Computational Efforts***

High Mach Turbine CFD Analysis

High Mach Turbine Integrated  
Inlet/ Fan Analysis

## ***NRA's***

**Techland:** Mode Transition  
Strategies for TBCC inlets

**Boeing:** Flowpath Integration for  
TBCC Propulsion Systems

**Spiritech:** TBCC Dynamic  
Simulation Model Development



---

# **Combined Cycle Engine Large Scale Inlet Mode Transition Testing NASA GRC 10X10 SWT**



**&**

# **Integrated Flowpath Computational Efforts**



# CCE Inlet and Controls research in the GRC 10x10 SWT

## Supported by both TBCC and GNC Disciplines




### Test Approach - 4 Phases

1. Inlet performance and operability characterization, Mode Transition Sequencing
2. System Identification of inlet dynamics for controls
3. Demonstrate Control strategies for smooth & stable mode transition without inlet unstart
4. Add turbine engine/ nozzle for integrated system test with simulated Scramjet

### **Testbed Features**

- Variable Low Speed Cowl
- Variable High Speed cowl
- Variable Ramp
- Variable Compartmented Bleed (13)
- Low Speed Mass flow / Backpressure Device
- High Speed Mass flow / Backpressure Device
- Inlet Performance Instrumentation (~800)
- Engine Face: Flow Characteristics (AIP)


# CY10 - CCE LIMX Build-up and Installation





# CCE LIMX Installed in NASA 10X10 SWT

(Phase I - Testing On-Going- Status next Presentation)



# CCE LIMX CFD Effort




## Objectives of Pre-Test LIMX CFD Analyses:

- Characterize the turbulent boundary layers and shock waves within the low and high-speed flowpaths under back-pressure.
- Evaluate performance of the low-speed flowpath as characterized by bleed and engine flow rates and total pressure recovery.
- Evaluate the total pressure distortion at the turbfan face.
- Evaluate the effectiveness of porous bleed and vortex generators.
- Explore sensitivities to variations in low-speed ramp angle and back-pressure for development of inlet controls.


$$p_{AIP}/p_{iso,ref}=2.28$$

$$A_t/A_{AIP}=83\%$$




Variation in static pressure with back-pressure in the high-speed flowpath.

Shock structure through the high-speed flowpath.



Mach number through the low-speed flowpath.



Total pressures distortion at the engine face.

# Bleed Modeling



## Elements of Modeling:


- The low-speed flowpath of the LIMX incorporates 13 separate porous bleed regions to minimize adverse effects of the shock / turbulent boundary layer interactions.
- Bleed rates may vary over the bleed region in response to shock waves within the flow field.
- Modeling evaluates bleed rates and bleed plenum pressures based on local flow conditions and plenum exit conditions (fixed-area, choked exits).

## Computational Efforts:


- Models incorporated into Wind-US and BCFD for LIMX simulations.
- Models incorporated into PEPSI-S PNS solver.

## Experimental Efforts:

- Test of bleed holes in 15x15 cm supersonic wind tunnel facility in FY11.
- CCE LIMX testing in 10x10 ft facility in FY11.
- CCE IMX testing in 1x1 ft facility with variable bleed regions.



Mach number and bleed velocity vectors on the symmetry plane.



Variation of bleed velocity vectors in the R4 bleed region.



# **High Mach Fan Rig Testing NASA W8 Compressor Facility**

**&**

# **Component Technology Computational Efforts**



# TBCC Fan Stage Operability and Performance




Fan Rotor Blisk



Inlet Distortion Screens

RTA: GE 57 / NASA Mach 4 capable TBCC Engine




**FAN STAGE = Rotor + OGV + Fan Frame Strut**


## Approach:

- Perform sub-scale testing of a relevant Mach 4 turbine engine fan stage in the NASA W8 high speed compressor facility.
- Predict performance & operability prior to test using SOA analysis tools.
- Map fan stage performance and measure stall line stability boundary over wide range of engine operation and compare to pre-test predictions.
- Incorporate inlet distortions and quantify performance & operability
- Assess the capability of SOA tools to predict results with flow distortions
- Utilize test article to understand physics and improve models.


# High Mach Fan Rig Test Distortion Screens




**Uniform Flow**




**Distortion Screen #2  
Circumferential**




**Distortion Screen #4  
Based on CCE CFD #1**



**Distortion Screen #1  
Sector**



**Distortion Screen #3  
Sinusoidal**





**Distortion Screen #5  
Based on CCE CFD #2**



# Example: IMPACT OF DISTORTION : 50% Reduction in Stall Margin (due to 10% Total Pressure Deficit - High Mach Fan Rig Results to be Presented)



## 95 % Speed Effect of Distortion



10% Deficit in Total Pressure

# Computational Efforts - Flow Solvers

## (Complex 3-D RANS)



### APNASA

- Average-Passage Equation System
- Multi-stage turbomachinery code
- Finite Volume Formulation (Central Differencing)
- Multiple exit flow paths capability
- Cylindrical Coordinate System (LHR)
- 4-stage Runge-Kutta with convergence accelerators
- $k$ - $\epsilon$  turbulence model with wall damping fcn
- Real gas model
- Steady state analysis
- Boundary Conditions
  - Uniform Flow or Radial Profile
  - Total Conditions and flow angles specified at Inlet
  - Specified static pressure and/or massflow at Exit

Uniform Flow or Radial Profile – Has been used as input for Unsteady Analysis - 1 day turn around

### TURBO

- MPI-Implemented multi-block parallel code
- Full annulus or phase-lag multi-stage turbomachinery code
- Finite volume discretization, flux splitting upwind scheme
- Multiple exit flow paths capability
- Cartesian Coordinate System
- Implicit iterative Newton algorithm
- 3-D unsteady Reynolds-averaged Navier-Stokes rotation frame formulation
- $k$ - $\epsilon$  turbulence model with wall damping fcn
- Real gas model
- Flutter simulation capability
- Boundary Conditions
  - Uniform flow or with flow distortion
  - Total Conditions and flow angles specified at Inlet
  - Specified static pressure and/ or massflow at Exit

Flow Distortion & Unsteady – 1 week turn around

# High Mach Fan Computational Results (example TURBO)






inlet

rotor

OGV

strut



inlet : 5x39x81x51

rotor : 25x169x81x51, [71x81x51]

OGV : 48x133x81x51, [87x81x51]

strut : (6x156x41x201)x2, [61x41x201]



## Ground Experiment

Williams International Modified WJ-38-15  
High Mach Turbine Engine



# Williams WJ38 Modifications For Mach 3 Operation & Wind Tunnel Integrated Inlet Test



- **Expanded operational envelope to accommodate**
  - ✓ SLS development tests
  - ✓ Mach 3 capable (Base engine M 0.9)
- **Increase T2 temperature capability (fan stage, housing, bearings, rub strips)**
  - ✓ New distortion tolerant fan stage, bypass duct, liners, high specific flow fan and IGV
  - ✓ All new hardware downstream of turbine (AB design from IR&D program )
- **SLS testing At WI**
  - ✓ Core engine test completed June 2010
  - ✓ Full AB, SERN Nozzle, High T abradable - April 2011
- **Engine Delivery 2<sup>nd</sup> / 3<sup>rd</sup> Quarter FY11**
- **CCE TBCC integrated inlet / engine Test FY 2013 (Partnership Required)**



# Summary and Concluding Remarks Accomplishments Since FAP Atlanta



- **Provided an overview of the major tasks in the TBCC Discipline**
  - **Combined Cycle Engine Large Scale Inlet Mode Transition Experiment (CCE LIMX)**
  - **High Mach Fan Rig Experiment**
  - **High Mach Turbine Engine Development**
  - **Integrated Flowpath Computational Efforts**
  - **Component Technology Computational Efforts**
- **Major Achievements Since Last FAP**
  - **CCE LIMX Model and Supporting Hardware Fabrication Completed**
    - Very Complex Model with significant variable geometry
  - **CCE LIMX Installed into the GRC 10X10 SWT**
    - Researchers very particular on requirements and alignment
    - Numerous hardware, interface, and instrumentation issues were resolved in field
  - **CCE Phase I Testing Commenced (10X10 is a Continuous Flow Facility)**
  - **High Mach Fan Rig Testing Completed with Varying Flow Distortion Distributions in the NASA GRC W-8 Facility**
    - Flow Profile: Uniform, Radial, Sinusoidal, and Matching CCE LIMX CFD
  - **High Mach Turbine Engine Core Test Completed**

# Summary and Concluding Remarks

## Upcoming Activities & Potential Issues

---



- **FY11+ Key Deliverables and Milestones**
  - Large Scale Inlet Steady State Testing Completed
  - Large Scale Inlet Dynamics Testing Completed
  - High Mach Turbine Engine Acceptance Test Complete & Engine Delivered to NASA
  - Integrated Flowpath Computational Efforts – Post CCE Testing Analysis
  - Component Technologies Computational Efforts – Comparison to W-8 Test Data
  - FY12 – Large Scale Inlet Controlled Mode Transition Testing (Partnership Required)
  - FY13 – Large Scale Inlet Controlled Mode Transition Testing with Turbine Engine (Partnership Required)
- **Potential Issues/ Concerns**
  - **Complexity of CCE LIMX Model – Some Risk of Delays during Operation**
    - Significant variable geometry and continuous flow of 10X10 SWT enables much data to be obtained during each test (Phase I is on-going and proceeding well)
  - **Funding – Partnerships required to conduct some future activities**

# ACRONYMS



- **AFRL – Air Force Research Laboratory**
- **AIP – Aerodynamic Interface Plane**
- **CCE – Combined Cycle Engine**
- **CFD – Computational Fluid Mechanics**
- **DARPA – Defense Advanced Research Projects Agency**
- **DMSJ – Dual Mode ScramJet**
- **GE – General Electric, Inc.**
- **GNC – Guidance, Navigation, and Control (Discipline)**
- **IMX- Inlet Mode Transition Experiment (smaller scale in NASA GRC 1X1 SWT)**
- **LH2 – Liquid Hydrogen**
- **LIMX – Large Scale Inlet Mode Transition Experiment (in NASA GRC 10X10 SWT)**
- **LO2 – Liquid Oxygen**
- **OGV – Outlet Guide Vane**
- **M&S – Materials and Structures (Discipline)**
- **MDAO – Multi-Disciplinary Analysis and Optimization (Discipline)**
- **RATTLRS – Revolutionary Approach To Time critical Long Range Strike (missile concept)**
- **SOA – State Of the Art**
- **SSTO – Single Stage To Orbit**
- **SWT – Supersonic Wind Tunnel**
- **TBCC – Turbine Based Combined Cycle (Discipline)**
- **WI – Williams International, Inc.**



